



Quick Antenna Connection Check for Delphi MyFi XM2GO

If no reception is received, the antenna connections may be disconnected. This guide presents a quick way to check the connections.

Written By: Scott Byer





TOOLS:

- [Spudger](#) (1)
-

Step 1 — Removing Delphi MyFi XM2GO Battery Cover



- Flip the Delphi MyFi XM2GO Device on its back to start the cover-removal process.
- The back cover is the access point for the user-removable battery. Removing the back cover also gives the user access to the hard-reset button.

Step 2



- Locate the large button on the top back of the device. This button is used to release the latch holding the sliding back cover in place.
- Press this button at the top while making a firm grip on the battery cover.
- As the button is pressed, move the cover towards the bottom of the device while applying moderate pressure to the cover.
- Be careful to not press down too hard on the battery cover as it is made of plastic.
- The battery removal tab may pop up during the cover removal process.

Step 3



- After the cover is removed, the white Lithium Ion battery is visible.

Step 4 — Removing Delphi MyFi XM2GO Battery



- Removing the back cover allows access to the user-removable battery.
- Should the battery need to be replaced or swapped, following these steps will aid in the process.
- The battery comes from the manufacturer with a pull tab with a web address printed on it to direct the user in purchasing a new battery.
- Holding the device, grab the tab with thumb and index figure.

Step 5



- Pull down on the tab so that the battery block moves a few millimeters towards the bottom of the device.
- The battery will move parallel to the back of the device while a latch at the top is freed with the downward motion.
- There is a pivot point at the bottom of the battery where the contacts connect to the battery.
- After the latch at the top is disengaged, pivot the battery away from the back and the battery will be free.

Step 6



- With the battery removed, the back of the device reveals more information about the product.

Step 7 — Quick Antenna Connection Check for Delphi MyFi XM2GO



- Under the battery is a magnetic mat, shown in red, that shields battery interference with the reception of the XM Satellite antenna.
 - This mat is stuck to the back of the device like a sticker and can be removed.
- ⚠ **CAUTION:** Do not operate the device without this magnetic shield.

Step 8



- On the bottom left side of the magnetic mat, the corner can be lifted up to reveal the U.FL antenna connector. A spudger or your fingernails can be used to pry up the corners.
- These U.FL antenna connections are standard for most portable devices and WiFi cards. They may become detached through use and may be checked if no reception is present.
- Lift up the corner and notice the two connectors going to the PCB.

Step 9



- Both of these connectors must be firmly attached to the PCB. Try pressing them firmly to make sure they are making full contact.

Step 10



- On the top right corner, the magnetic mat can be lifted up to check another U.FL connector as with the 3rd step.
- This mat can be pressed down again to secure after checking the connector.

Step 11



- Try pressing down on the U.FL connector, as seen in this picture, to ensure a secure connection.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-07-11 12:38:43 AM.